

Fabricant français  
depuis 1964

[www.gys.fr](http://www.gys.fr)



# COMMENT CHOISIR SES GALETS ?



## B. Types de galet selon poste à souder

PRODUIT	Type de galet	Qt galet	Galet moteur	Galet origine	Fil fourré				Fil plein acier / inox				Fil plein alu				Bobine de fil MIG / MAG			
					0.6	0.9-1.0	1.2	1.6	2.0	2.4	0.6	0.8	1.0	1.2	1.6	0.8	1.0	1.2	1.6	Ø100
<b>SMARTMIG</b>																				
142	A	2	1	35°V - 0.6 / 0.8																
152	A	2	1	35°V - 0.6 / 0.8																
162	A	2	1	35°V - 0.6 / 0.8																
182	A	2	1	35°V - 0.6 / 0.8																
<b>MONOGYS</b>																				
200-4CS	A	4	2	35°V - 0.8 / 1.0																
250-4CS	B	4	2	35°V - 0.8 / 1.0																
320-4CS	B	4	2	35°V - 1.0 / 1.2																
<b>EASYMIG</b>																				
85	D	2	1	90°V cranté - 0.6 / 0.9																
130	D	2	1	35°V - 0.8 / 90°V cranté - 0.9																
150	A	2	1	35°V - 0.8 / 90°V cranté - 0.9																
160	A	2	1	35°V - 0.8 / 90°V cranté - 0.9																
<b>MULTIPEARL</b>																				
210-2	A	2	1	35°V - 0.6 / 0.8																
210-4 XL	B	4	2	35°V - 0.6 / 0.8																
211-4	B	4	2	35°V - 0.6 / 0.8																
<b>MULTIWELD</b>																				
180M-C	A	4	2	35°V - 0.8 / 90°V cranté - 0.9																
200M	A	2	1	35°V - 0.8 / 1.0																
200M-C	A	4	2	35°V - 0.8 / 1.0																
FV 220M-C	A	4	2	35°V - 0.8 / 1.0																
250T-C	A	4	2	35°V - 0.8 / 1.0																
320T-C	B	4	2	35°V - 0.8 / 1.0																
200M	A	4	2	35°V - 0.8 / 1.0																
FV 220M	A	4	2	35°V - 0.8 / 1.0																
250T	A	4	2	35°V - 0.8 / 1.0																
320T	B	4	2	35°V - 0.8 / 1.0																
400T	B	4	2	35°V - 1.0 / 1.2																
<b>KRONOS</b>																				
250M	B	4	2	35°V - 0.8 / 1.0																
320T	B	4	2	35°V - 1.0 / 1.2																
400T Duo	B	4	2	35°V - 1.0 / 1.2																
400T W	B	4	2	35°V - 1.0 / 1.2																
<b>GALAXY</b>																				
250M	B	4	2	35°V - 0.8 / 1.0																
250T	B	4	2	35°V - 1.0 / 1.2																
320T	B	4	2	35°V - 1.0 / 1.2																
400T Duo	B	4	2	35°V - 1.0 / 1.2																
400T W	B	4	2	35°V - 1.0 / 1.2																
<b>WF</b>																				
35 / 36	B	4	2	35°V - 1.0 / 1.2																
50	F	4	4	35°V - 1.0 / 1.2																
<b>EXAGON</b>																				
EXAFEED-4L	C	4	2	35°V - 1.0 / 1.2																
NOMADFEED 425-4 CC/CV	E	4	2	35°V - 1.6																
	C			35°V - 1.2 / 1.6																
<b>NEOPULSE</b>																				
220 C	B	4	2	35°V - 0.8 / 1.0																
220 C XL	B	4	2	35°V - 0.8 / 1.0																
320 C	F	4	4	35°V - 1.0 / 1.2																
400 CW	F	4	4	35°V - 1.0 / 1.2																
400 G	F	-	-	-																
500 G	F	-	-	-																
NEOFEED-4W	F	4	4	35°V - 1.0 / 1.2																
SMARTFEED M-4	F	4	4	35°V - 1.0 / 1.2																
<b>E GYS AUTO</b>																				
E1	B	4	2	35°V - 0.6 / 0.8																
E2	B	4 (x2)	2	U - 0.8 / 1.0																
				35°V - 0.6 / 0.8																
E3	B	4 (x3)	2	U - 0.8 / 1.0																
				35°V - 0.6 / 0.8																
				35°V - 0.8 / 1.0																
<b>P GYS AUTO</b>																				
P1	B	4	2	U - 1.0 / 1.2																
P2	B	4 (x2)	2	U - 1.0 / 1.2																
				35°V - 0.8 / 1.0																
P3	B	4 (x3)	2	U - 1.0 / 1.2																
				35°V - 0.8 / 1.0																
				35°V - 0.6 / 0.8																
<b>AUTOPULSE</b>																				
220-M1	B	4	1	U - 1.0 / 1.2																
220-M3	B	4 (x3)	2	35°V - 0.6 / 0.8																
				35°V - 0.8 / 1.0																
				U - 1.0 / 1.2																
320-T1	B	4	4	U - 1.0 / 1.2																
320-T3	B	4 (x3)		35°V - 0.6 / 0.8																
				35°V - 0.8 / 1.0																
				U - 1.0 / 1.2																